

**500W-3000W, AC AND DC INPUT MODELS**

# 9000 RAIL BATTERY CHARGER



## Features

- » 230 VAC and 400 VAC input models
- » 110 VAC input model
- » Efficiency up to 95 %
- » Forced cooling with fan
- » MTBF 1 800 000 h
- » Output models 24, 36, 110 VDC
- » 500W, 1500W and 3200W models
- » Coated PCB for rail and metro applications
- » Large operation temperature range from -40 °C to +55 °C and up to +70°C with derating

## Product description

ADC9000 series battery management and power modules are the flagship solutions for rail industry. This rugged and versatile series is rail approved according to the highest standards. Track record is field proved by major rail manufacturers world-wide. Modules are utilizing forced cooling for lowest possible footprint and total volume, saving valuable space. Communication via Ethernet (TRDP) and/or CAN-bus enabled for 3kW products.

## Standards

- » EN50155:2007 Railway applications – Electronic equipment used on rolling stock
- » EN50124-1:2001 Railway applications – insulation coordination
- » EN50153:2014 Railway applications – Rolling stock – Protective provisions relating to electrical hazards
- » EN45545-2:2013: Railway applications – Fire protection on rail vehicles
- » EN61373:2010: Railway applications - Shock and vibration

# Technical Specifications

AC input	ADC9040	ADC9942 ADC9944	ADC9982	ADC9953
<b>Input voltage</b>	1x230 VAC rms (+15 % / -20 %)	3x400 VAC rms (+15 % / -20 %)	3x400 VAC rms (+15 % / -20 %)	3x400 VAC rms (+15 % / -20 %)
<b>Input current</b>	2,5 Arms	5,5 Arms	5,5 Arms	5,5 Arms
<b>Inrush current</b>		12A peak/phase	12A peak/phase	12A peak/phase
<b>Input frequency</b>	47...63 Hz	47...63 Hz	47...63 Hz	47...63 Hz
<b>External circuit breaker</b>	10A	16A	16A	16A
<b>Nominal output voltage</b>	29 VDC	24 VDC	36 VDC	110 VDC
<b>Output voltage adjustment range</b>		21...32 VDC	25,2...45 VDC	100...137 VDC
<b>Overvoltage protection</b>		35 V	50 V	145 V
<b>Maximum output current</b>	23 A	100...133 A	71,9...88,9 A	23...29 A
<b>Maximum output power</b>	550 W	3200 W	3200 W	3200 W
<b>Efficiency</b>	90...93 %	90...93 %	90...93 %	90...93 %
<b>Regulation</b>	Voltage $\pm 1$ %	Voltage $\pm 1$ %	Voltage $\pm 1$ %	Voltage $\pm 1$ %
<b>Output voltage adjustment</b>		ADC9942 via CAN bus ADC9944 also via Ethernet	Via CAN bus	Via CAN bus
<b>Output ripple voltage</b>	<50 mVRMS	ADC9942 <150mVRMS ADC9944 <75 mVRMS	<150mVRMS	<150mVRMS
<b>Rev.-polarity-protection</b>	Mechanical	Mechanical	Mechanical	Mechanical
<b>Ethernet (TRDP)</b>	No	ADC9944	No	No
<b>CAN</b>	No	ADC9942 and ADC9944	Yes	Yes
<b>Ambient temperature</b>	-40 °C to +55 °C +70°C with derating	-40 °C to +55 °C +70°C with derating	-40 °C to +55 °C +70°C with derating	V C
<b>Dimensions Width x height x depth</b>	175 x 112 x 250 mm	220 (290) x 88 (105) x 400mm	220 (290) x 88 (105) x 400mm	220 (290) x 88 (105) x 400mm

110VDC input	DDC9870	DDC9961	DDC9970
<b>Input voltage</b>	110 VDC (-30% ... +25%)	110 VDC (-30% ... +25%)	110 VDC (-30% ... +25%)
<b>Input current</b>	13 A	26 A	26 A
<b>Inrush current</b>	< 5 A	< 5 A	< 5 A
<b>External circuit breaker</b>	25 A	40 A	40 A
<b>Input fusing</b>	external	external	external
<b>Nominal output voltage</b>	24 VDC	24 VDC	28 VDC
<b>Overvoltage protection</b>	30 V	30 V	30 V
<b>Maximum output current</b>	63 A	110 A	110 A
<b>Maximum output power</b>	1500 W	3000 W	3000 W
<b>Efficiency</b>	91...95 %	91...95 %	91...95 %
<b>Regulation</b>	Voltage $\pm$ 0,5 %	Voltage $\pm$ 2,5 %	Voltage $\pm$ 2,5 %
<b>Output voltage adjustment</b>	Via CAN bus	Analog	Analog
<b>Output ripple voltage</b>	<120 mVRMS	<120 mVRMS	<120 mVRMS
<b>Ambient temperature</b>	-40 °C to +55 °C +70°C with derating	-40 °C to +55 °C +70°C with derating	-40 °C to +55 °C +70°C with derating
<b>Dimensions Width x height x depth</b>	146 mm x 86 mm x 398 mm	220 mm x 88 mm x 400 mm	220 mm x 88 mm x 400 mm